TABLE 2 - Test Turn Around and Fee Table

Holidays and weekends are not included in test turn around times.

Turn Around Time - Is the amount of time where preliminary results are required to be available to CCPW after sampling has occurred.

| | Time - Is the amount of time where preliminary results are required to be available to CCPW after sampling | | | |
|-------------------------------|--|---------------------------|-----------------------|----------------|
| Upload Time - I | s the number of days until results are required to be uploaded into project management software after samp | ling has occured. | | |
| | SOILS AND AGGREGATE | <u> </u> | | |
| Testing Standard | Description | Turn Around Time (Hrs) | Upload Time (Days) | Testing Fee |
| AASHTO T11 | Material Finer Than the 75-um (No.200) Sieve | 24 | 2 | \$100 |
| AASHTO T19 | Unit Weight and Voids in Aggregates | 24 | 2 | \$100 |
| AASHTO T21 | Organic Impurities in Fine Aggregate for Concrete | 24 | 2 | \$100 |
| AASHTO T27 | Sieve Analysis of Fine and Coarse Aggregates | 24 | 2 | \$125 |
| AASHTO T84 | Specific Gravity and Absorption of Fine Aggregate | 72 | 4 | \$150 |
| AASHTO T85 | Specific Gravity and Absorption of Coarse Aggregate | 48 | 3 | \$150 |
| AASHTO T89 and T90 | Liquid Limit , Plastic Limit, and Plasticity Index of Soils | 72 | 4 | \$150 |
| AASHTO T96 | LA Abrasion | 48 | 3 | \$200 |
| AASHTO T104 | Soundness of Aggregates by Use of Sodium Sulfate | 168 | 8 | \$1,000 |
| AASHTO T112 | Clay Lumps and Friable Particles | 48 | 3 | \$75 |
| AASHTO T113 | Lightweight Pieces in Aggregate | 48 | 3 | \$150 |
| AASHTO T190 | Resistance R-Value and Expansion Pressure of Compacted Soils | 96 | 5 | \$500 |
| AASHTO T191 | Density and Unit Weight of Soils in Place by - Sand Cone Method | 24 | 3 | \$150 |
| AASHTO T238 | Density of Soil and Soil-Aggregate in Place by Nuclear Methods | 1 | 1 | \$50 |
| AASHTO T239 | Moisture Content of Soil and Rock in Place by Nuclear Methods | 1 | 1 | \$50 |
| AASHTO TP57 | Methylene Blue (Materials Passing #200 Sieve) | 72 | 4 | \$200 |
| AASHTO T99 | Moisture/Density Relationship of Soils | 72 | 4 | \$150 |
| AASHTO T180 | Laboratory Compaction Characteristics of Soil Using Modified Effort (Granular Material) | 72 | 4 | \$150 |
| | , , | | | , |
| | Laboratory Compaction Characteristics of Soil Using Modified Effort (Clay and Silt Material) | 96 | 5 | \$150 |
| Cal-Trans 227 | Cleanness Value | 48 | 3 | \$150 |
| AASHTO T335 | Determining Percent of Fractured Faces | 24 | 2 | \$100 |
| AASHTO T289 & AASHTO 288 | Ph and Electrical Resistance | 72 | 2 | \$50 |
| AASHTO T265 | Laboratory Determination of Water (Moisture) Content of Soil and Rock | 24 | 2 | \$50 |
| AASHTO T176 | Sand Equivalent Value of Soils and Fine Aggregates | 48 | 3 | \$125 |
| ASTM D4791 | Flat and Elongated Particles in Coarse Aggregates | 24 | 2 | \$150 |
| USS 704.03.07.D ASTM D4832 | Preparation and Testing of CLSM Samples | 24 ACT | 1 ACT | 200/set |
| ASTM D1633 A | Compressive Strength of Molded Soil-Cement Cylinders | 24 ACT | 1 ACT | \$25 |
| AWWA 3500-NaD | Total Available Water Soluble Sulfates | 120 | 5 | \$150 |
| AWWA 4500E | | 120 | 5 | \$150 |
| AASHTO T290B | Soluble Sulfates in Soils | 120 | 5 | \$225 |
| AASHTO T104 | Magnesium Sulfate Sounfness | 120 | 5 | \$225 |
| AASHTO T291A | Free Chlorides in Soils | 120 | 5 | \$225 |
| AASHTO T236 | Direct Shear | 48 | 5 | \$125 |
| | ASPHALTIC BINDER | | _ | <u> </u> |
| Testing Standard | Description | Turn Around | Upload Time | Acceptance Fee |
| AASHTO T49 | Penetration of Bituminous Materials | Time (Hrs) | (Days) | \$75 |
| AASHTO T59 | Emulsified Asphalts | 48 | 3 | \$300 |
| AASHTO T72 | Saybolt Viscosity | 48 | 3 | \$125 |
| AASHTO T313 | PAV Aged - Method for Determining Flexural Creep Stiffness of Asphalt Binder Using the Bending | 72 | 4 | \$500 |
| | Beam Rheometer (BBR) | | | |
| AASHTO T314 | PAV Aged - Direct Tension | 72 | 4 | \$500 |
| AASHTO T315 | PAV Aged - Rheological Properties of Asphalt Binder Using a Dynamic Shear Rheometer (DSR) | 72 | 4 | \$500 |

Ductility of Bituminous Materials @ 4° C

24

\$100

NDOT T746

| T .: 0: 1 1 | HOTMIX ASPHALT | TT A 1 | Upload Time | |
|-------------------|--|---------------------------|-----------------------|----------------|
| Testing Standard | Description | Turn Around Time (Hrs) | (Days) | Accept Fee |
| AASHTO T164 | Quantitative Extraction of Bitumen from Bituminous Paving Mixtures | 24 | 2 | \$15 |
| AASHTO T245 | Resistance to Plastic Flow of Bituminous Mixtures Using Marshall Apparatus | 24 | 2 | \$300 |
| AASHTO T275 | Bulk Specific Gravity and Density of Compacted Bituminous Mixtures Using Paraffin Coated Specimens | 24 | 2 | \$50 |
| AASHTO T209 | Theoretical Maximum Specific Gravity and Density of Bituminous Paving Mixtures | 2 | 1 | \$10 |
| AASHTO T355 | Density of Bituminous Concrete in Place by Nuclear Method | 1 | 1 | 50/te |
| AASHTO T308 | Determining the Asphalt Content of Hot Mix Asphalt (HMA) by Ignition Method | 6 | 1 | \$20 |
| **AASHTO T283 | Resistance of Compacted Asphalt Mixture to Moisture-Induced Damage | 84 | 6 | \$45 |
| *AASHTO T340 | Determining the Rutting Susceptibility of HMA using the Asphalt Pavement Analyzer (APA) | 72 | 4 | \$800 / |
| | CONCRETE | | | |
| Testing Standard | Description | Turn Around Time (Hrs) | Upload Time (Days) | Accepta Fee |
| ASTM C39 | Compressive Strength of Cylindrical Concrete Specimens | 24 ACT | 1 ACT | 100/set |
| ASTM C31 | Making and Curing Concrete Test Specimens in the Field | NA | NA | 100/ho |
| ASTM C42 | Obtaining and Testing Drilled Cores and Sawed Beams of Concrete | 24 | 2 | 160/ho |
| ASTM C40 | Effect of Organic Impurities in Fine Aggregate on Strength of Mortar | 672 | 30 | \$2,50 |
| NDOT T442G | Flexural Strength of Concrete (Using Simple Beam with Third-Point Loading) | 24 ACT | 1 ACT | 75/ea |
| ASTM C143 | Slump of Hydraulic Cement Concrete | 1 | 1 | \$50 |
| ASTM C138 | Unit Weight, Yield, and Air Content (Gravimetric) of Concrete | 1 | 1 | \$75 |
| ASTM C192 | Making and Curing Concrete Test Specimens in the Laboratory | NA | NA | 100/ho |
| ASTM C231 | Air Content of Freshly Mixed Concrete by the Pressure Method | 1 | 1 | \$12: |
| ASTM C173 | Air Content of Freshly Mixed Concrete by the Volumetric Method | 1 | 1 | \$12: |
| ASTM C567 | Unit Weight of Freshly Mixed Structural Lightweight Concrete | 1 | 1 | \$75 |
| ASTM C1107/ C109 | Compressive Strength of Grout either by Cubes or Cylinder (1-set) | 24 ACT | 32 | \$100/3 |
| ASTM C1107/ C109 | Compressive Strength of spall repair patch material | 24 ACT | 32 | \$100/ |
| | COATINGS | | | |
| Testing Standard | Description | Turn Around | Upload Time | Accepta |
| ASTM D1400 | Nondestructive Measurement of Dry Film Thickness of Nonconductive Coatings Applied to a Nonferror Metal | Time (Hrs) | (Days) | Fee \$25 |
| Fed Spec TT-E-489 | Paint Thickness | 1 | 1 | \$25 |
| • | STEEL | | | |
| Testing Standard | Description | Turn Around Time (Hrs) | Upload Time (Days) | Accepta |
| AASHTO T244 | Test Methods and Definitions for Mechanical Testing of Steel Products | 48 | 3 | 125/b |
| ASTM E709 | Practice for Magnetic Particle Examination | EOD | 2 | 250/ho |
| AWS D2.0 | Welding Inspection | EOD | 2 | 250/ho |
| ASTM A615 | Ultimate Tensile Strength - Completed prior to placement of concrete on structures | 48 | 3 | 125/b |
| | TRAFFIC MARKINGS | _ | | |
| Testing Standard | Description | Turn Around Time (Hrs) | Upload Time (Days) | Accepta Fee |
| ASTM D711 | No-Pick-Up Time of Traffic Paint | 24 | 2 | 100/ho |
| | Legend: | | | |
| | ACT = After Completion of Test | | | |
| | EOD = End of the Day | | | |